

Ethylene Glycol Monomethyl Ether (EM)

Product No.	D011
CAS No.	109-86-4
Molecular formula	CH ₃ OCH ₂ CH ₂ OH
Other name	2-Methoxyethanol, Methyl cellosolve, EM

Specifications

Appearance	Colorless transparent liquid
Assay ≥%	99.50
Water ≤%	0.2
Distillation Range (760mmHg°C)	123.5-127.0
Specific Gravity (d ₄ ²⁰)	0.9646±0.005
Color(Pt-Co) ≤	15

Application: EM is mainly used as solvent for grease, nitrocellulose, synthetic resin, alcoholate dyestuff and vinylcellulose. In coating industry, it can be used as varnish dryer and coating diluent. In printing and dyeing industry, it can be used as osmosis reagent and leveling agent. It also can be used as additive in fuel industry and dyestuff in textile industry and as organic synthesis intermediate.

Packing: Coated steel drum (190 or 200kg/drum)
ISO tank (20MT)

Handling: Please download MSDS and print as many as needed for handling instruction.

Contact us:

Luke Verdet

Director - North America Marketing

Tel & Voice mail: 1.914.965.2077 / Fax: 1.914.375.2093

Email: luke.verdet@dynamicna.com / verdetl@aol.com

Jim Ye

Director - Business Development

Tel & Voice mail: 1.914.613.3386 / Fax: 1.914.375.2093

Email: jim.ye@dynamicna.com / jimzye@gmail.com