

Propylene Glycol Monomethyl Ether Acetate (PMA)

Product No.	D006
CAS No.	108-65-6
Molecular formula	CH ₃ COOCH(CH ₃)CH ₂ OCH ₃
Other name	1-Methoxy-2-acetoxyp propane, Propylene glycol methyl ether acetate, PMA, PGMEA

Specifications

Appearance	Colorless transparent liquid
Assay ≥%	99.50
Water ≤%	0.05
Acidity (as HAC) ≤%	0.02
Distillation Range (760mmHg°C)	143.0-149.0
Isomer ≤%	0.4
Specific Gravity (d ₄ ²⁰)	0.965-0.975
Color(Pt-Co) ≤	10

Application: They are excellent industrial solvents with low toxicity and have strong solubility for polar and unpolar materials, which can be used for advanced paints, printing inks as well as some other polymers, including amido, methyl ester, ethyl, polyester, cellulose acetate, glycol acid resin, acrylic acid resin, epoxy resin and nitrocellulose etc. And PMP is the best solvent for paints and printing inks, which is suitable for unsaturated polyester, polyurethane, acrylic acid resin and epoxy resin etc.

Packing: Coated steel drum (200kg/drum)
ISO tank (20MT)

Storage: Cool, dry and well ventilated condition.

Handling: Please download MSDS and print as many as needed for handling instruction.

Contact us:

Luke Verdet

Director - North America Marketing

Tel & Voice mail: 1.914.965.2077 / Fax: 1.914.375.2093

Email: luke.verdet@dynamicna.com / verdetl@aol.com

Jim Ye

Director - Business Development

Tel & Voice mail: 1.914.613.3386 / Fax: 1.914.375.2093

Email: jim.ye@dynamicna.com / jimzye@gmail.com